Spółdzielnia - Zakład Pracy Chronionej
21-300 Radzyń Podlaski ul. Gen. Fr. Kleeberga 10

Air pressure fall sensor

Voltage rating: 12 V or 24 V
Power rating: 48 W
Max. safe pressure 2943 kPa
Applications: trucks, buses, farm and building and other machines



Part number	Required pressure	Kind of thread	Terminal variety
502.13.20	$490^{\pm 49}$ kPa ($5^{\pm 0,5}$ kG/cm^2)	Metric thread12 x 1,5	Flat
502.16.20	$539^{\pm 49}$ kPa ($5,5^{\pm 0,5}$ kG/cm^2)		Flat

Voltage rating: 12 V or 24 V
Power rating: 48 W
Max. safe pressure 2943 kPa



Part number	Required pressure	Kind of thread	Terminal variety	Applications
502.20.20	$392^{\pm 39}$ kPa ($4^{\pm 0,4}$ kG/cm^2)	Metric thread12 x 1,5	Flat	Tractor Ursus, MF
502.30.20	$490^{\pm 49}$ kPa ($5^{\pm 0,5}$ kG/cm^2)	Metric thread12 x 1,5	Flat	Kamaz truck
502.32.20	$294^{\pm 29}$ kPa ($3^{\pm 0,3}$ kG/cm^2)	Taper thread 10 x 1 /cone/	Flat	Automatic lathe AS

CERTYFIKAT ISO 9001 SYSTEMU JAKOŚCI
TÜV CERT ISO 9001:2000 ZN: 75.100.6653 TÜV Rheinland InterCert
NIP:538-000-27-51
Home Office (083) 352 84 10
Trade Department (083) 352 84 42 fax 352 86 19
www.simena.com.pl
poczta@simena.com.pl
sprzedaz@simena.com.pl